

View Online at <https://aerobasegroup.com/nsn/5950-00-063-4198>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.093 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.470 inches

Body Width:

1.062 inches

Body Height:

0.907 inches

Distance Between Mounting Facility Centers:

1.270 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

10.0 milliamperes ac single component single secondary

Winding Operating Voltage:

31.00 ac volts single component single secondary and 1.00 ac volts single component single secondary and 1.60 ac volts single component single secondary and 2.00 ac volts single component single secondary and 2.20 ac volts single component single secondary and 2.50 ac volts single component single secondary

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0