NSN 5950-00-063-6706

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-063-6706

Thread Class (non-core):
2a single group
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.370 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.500 inches single mounting facility single center group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core single component
Body Length:
5.310 inches
Body Width:
4.430 inches
Body Height:
5.180 inches
Inclosure Type:
Partially enclosed, double shell
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
2 primary and 5 secondary single component
Cubic Measure (non-core):
121.2 cubic inches
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.190 inches single group
Winding Operating Current:
0.55 amperes ac single component single secondary
Winding Operating Voltage:
115.00 ac volts and 230.00 ac volts single component single secondary
Thread Series Designator:
Unf single group
Terminal Type And Quantity:

17 eyelet

NSN 5950-00-063-6706

Power Transformer - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0