NSN 5950-00-063-6809

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-063-6809

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

8.188 inches

Body Width:

4.063 inches

Body Height:

5.063 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

8.0 amperes ac single component 2nd secondary

Winding Power Rating:

4.1 kilovolt-amperes single component all secondary

Winding Operating Voltage:

300.00 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

NSN 5950-00-063-6809

Power Transformer - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0