

View Online at <https://aerobasegroup.com/nsn/5950-00-069-0314>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.047 inches single mounting facility single center group and 5.078 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.995 inches single mounting facility single center group and 4.005 inches single mounting facility single center group

Overall Height:

5.531 inches

Mounting Hole Diameter:

0.203 inches single group

Frequency Rating:

45.0 hertz single component and 430.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 5.406 inches and 5.468 inches

Body Width:

Between 5.031 inches and 5.093 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

10 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 9 secondary single component

Winding Operating Current:

1.4 amperes ac single component 4th secondary

Winding Operating Voltage:

76.80 ac volts single component 1st secondary

Special Features:

1 primary winding; 9 secondary windings

Test Data Document:

13499-672-0135-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

29 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0