

View Online at <https://aerobasegroup.com/nsn/5950-00-069-0314>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

5.047 inches single mounting facility single center group and 5.078 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.995 inches single mounting facility single center group and 4.005 inches single mounting facility single center group

**Overall Height:**

5.531 inches

**Mounting Hole Diameter:**

0.203 inches single group

**Frequency Rating:**

45.0 hertz single component and 430.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

**Body Length:**

Between 5.406 inches and 5.468 inches

**Body Width:**

Between 5.031 inches and 5.093 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

10 single group

**Mounting Method:**

Flange single group and unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 9 secondary single component

**Winding Operating Current:**

1.4 amperes ac single component 4th secondary

**Winding Operating Voltage:**

76.80 ac volts single component 1st secondary

**Special Features:**

1 primary winding; 9 secondary windings

**Test Data Document:**

13499-672-0135-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

29 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0