

View Online at <https://aerobasegroup.com/nsn/5950-00-069-2443>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

8.500 inches

Body Width:

4.250 inches

Body Height:

4.250 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary, variable autotransformer type single component

Thread Qty Per Inch (tpi):

28 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

3.0 amperes ac single component single secondary

Winding Power Rating:

1.7 kilovolt-amperes single component single secondary

Winding Operating Voltage:

480.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

14 terminal block w/screws

Reference Number Differentiating Characteristics:

As differentiated by electrical ratings and w/cut down shaft 0.750 in.From face of transformer

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0