

View Online at <https://aerobasegroup.com/nsn/5950-00-069-8161>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.500 inches single mounting facility single center group

Mounting Hole Diameter:

0.203 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

6.750 inches

Body Width:

4.750 inches

Body Height:

3.750 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

3.15 amperes ac single component 1st secondary and 3.5 amperes ac single component 1st secondary and 3.85 amperes ac single component 1st secondary

Winding Operating Voltage:

3.50 ac volts single component 1st secondary and 22.50 ac volts single component 1st secondary and 27.50 ac volts single component 1st secondary

Terminal Type And Quantity:

21 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0