NSN 5950-00-070-1586

Reactor - Page 1 of 2

Reliability Indicator:



View Online at https://aerobasegroup.com/nsn/5950-00-070-1586

Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.250 inches single mounting facility single center group **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.125 inches single mounting facility single center group **Inductance Type:** Fixed **Inductance Rating:** 120.00 millihenries single component single winding **Body Length:** 1.750 inches **Body Width:** 1.625 inches **Body Height:** 2.188 inches **Maximum Operating Temp:** 105.0 degrees celsius **Winding Quantity:** 1 single component Inclosure Type: Hermetically sealed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded stud single group **Rating Method:** Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group **Thread Size:** 0.138 inches single group **Winding Operating Current:** 300.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 2.800 single component single winding **Thread Series Designator:** Unc single group **Terminal Type And Quantity:**

N/a

Shelf Life:

2 standoff, solder lug

NSN 5950-00-070-1586

Reactor - Page 2 of 2



| | • • | | | |
|-------|-----|-------------|------|------|
| n | 1+ | <i>(</i>)+ | Meas | uro. |
| | | | | |

--

Demilitarization:

No

Fiig:

A058b0