

View Online at <https://aerobasegroup.com/nsn/5950-00-071-5914>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility single center group

Mounting Hole Diameter:

0.125 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and mounting single component

Body Length:

2.000 inches

Body Width:

1.000 inches

Body Height:

1.125 inches

Maximum Operating Temp:

71.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

50.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component 1st secondary

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0