

View Online at <https://aerobasegroup.com/nsn/5950-00-071-7708>

Thread Class (non-core):

Err-070

Thread Direction (non-core):

Err-070

Reliability Indicator:

Not established

Overall Length:

8.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.125 inches all mounting facilities 1st center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

7.000 inches all mounting facilities 2nd center group

Overall Height:

8.875 inches

Overall Width:

7.000 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

1.7 kilovolt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary and 1 secondary single component

Thready Qty Per Inch (tpi):

18 single group

Thread Size:

0.312 inches single group

Winding Operating Current:

12.0 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0