

View Online at <https://aerobasegroup.com/nsn/5950-00-073-1805>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.625 inches single mounting facility single center group and 0.937 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

1.828 inches

Body Width:

0.890 inches

Body Height:

1.234 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

56 single group

Thread Size:

0.086 inches single group

Winding Operating Current:

400.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

26.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0