

View Online at <https://aerobasegroup.com/nsn/5950-00-075-0504>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.880 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

1.690 inches

Body Width:

1.600 inches

Body Height:

2.870 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

750.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

4.60 ac volts single component single primary and 16.40 ac volts single component single primary and 39.00 ac volts single component single primary and 78.00 ac volts single component single primary and 87.80 ac volts single component single primary and 93.70 ac volts single component single primary and 115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0