NSN 5950-00-075-3427

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-075-3427 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.500 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.000 inches single mounting facility single center group |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.000 inches |
| Body Width: |
| 2.500 inches |
| Body Height: |
| 2.563 inches |
| End Application: |
| Wsd: sturgeon class ssn (637); general purpose electronic test equipment gpete |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 2 primary single component and 3 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 30.0 milliamperes ac single component 1st secondary |
| Criticality Code Justification: |
| Feat |
| Winding Operating Voltage: |
| 6.25 ac volts single component 3rd secondary |
| Special Features: |
| Weapon system essential |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 11 tab, solder lug |

Shelf Life: N/a

NSN 5950-00-075-3427Power Transformer - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

Demilitarization:

No

Fiig:

A058b0