

View Online at <https://aerobasegroup.com/nsn/5950-00-075-6743>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.500 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.060 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component and 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

3.540 inches

**Body Width:**

3.010 inches

**Body Height:**

3.880 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thready Qty Per Inch (tpi):**

24 single group

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

9.8 amperes ac single component 1st secondary

**Winding Operating Voltage:**

6.30 ac volts single component 2nd secondary

**Test Data Document:**

61497-99380 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

4 solder stud and 2 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0