Radio Frequency Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-076-0541

<ul> <li>Reliability Indicator:</li> <li>Not established</li> <li>Frequency Rating:</li> <li>480.0 kilohertz single component</li> <li>480.0 kilohertz single component</li> <li>Body Length:</li> <li>1.109 inches</li> <li>Body Outside Diameter:</li> <li>0.687 inches</li> <li>Distance Between Mounting Facility Centers:</li> <li>0.625 inches single mounting facility single center group</li> <li>1.625 inches single group</li> <li>1.605 unting Facility Quantity:</li> <li>2.531 group</li> <li>1.754 Data Document:</li> <li>1.3499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing</li> <li>1.754 Data Document:</li> <li>1.7554 Dat</li></ul>
Frequency Rating:         480.0 kilohertz single component         Body Length:         1.109 inches         Body Outside Diameter:         0.687 inches         Distance Between Mounting Facility Centers:         0.625 inches single mounting facility single center group         Inclosure Type:         Hermetically sealed         Mounting Facility Quantity:         2 single group         Mounting Method:         Threaded hole single group         Vinding Function And Quantity:         1 stape-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc: excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Incless Series Designator:         Unc single group         Japin
<ul> <li>480.0 kilohertz single component</li> <li>Body Length: <ul> <li>1.109 inches</li> </ul> </li> <li>Body Outside Diameter:</li> <li>0.687 inches</li> </ul> <li>Distance Between Mounting Facility Centers: <ul> <li>0.625 inches single mounting facility single center group</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Quantity: <ul> <li>2 single group</li> </ul> </li> <li>Mounting Method: <ul> <li>Threaded hole single group</li> <li>Winding Function And Quantity: <ul> <li>1 primary single component</li> <li>Test Data Document:</li> <li>13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)</li> <li>Thread Series Designator:</li> <li>Unc single group</li> <li>Terminal Type And Quantity:</li> <li>3 pin</li> </ul> </li> </ul></li></ul></li>
Body Length:         1.109 inches         Body Outside Diameter:         0.687 inches         Distance Between Mounting Facility Centers:         0.625 inches single mounting facility single center group         Inclosure Type:         Hermetically sealed         Mounting Facility Quantity:         2 single group         Mounting Method:         Threaded hole single group         Vinding Function And Quantity:         1 primary single component         Test Data Document:         13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Thread Series Designator:         Unc single group         Terminal Type And Quantity:         3 pin
1.109 inches         Body Outside Diameter:         0.687 inches         Distance Between Mounting Facility Centers:         0.625 inches single mounting facility single center group         Inclosure Type:         Hermetically sealed         Mounting Facility Quantity:         2 single group         Mounting Method:         Threaded hole single group         Vinding Function And Quantity:         1 primary single component         Test Data Document:         13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Thread Series Designator:         Unc single group         Jong Sapator:         Jong Jong         Jong Jong Jong Jong         Jong Jong Jong         Jong Jong Jong
Body Outside Diameter:         0.687 inches         Distance Between Mounting Facility Centers:         0.625 inches single mounting facility single center group         Inclosure Type:         Hermetically sealed         Mounting Facility Quantity:         2 single group         Mounting Method:         Threaded hole single group         Vinding Function And Quantity:         1 primary single component         Test Data Document         13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing)         etc:: excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Thread Series Designator:         Unc single group         Join
<ul> <li>0.687 inches</li> <li>Distance Between Mounting Facility Centers:</li> <li>0.625 inches single mounting facility single center group</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Quantity:</li> <li>2 single group</li> <li>Mounting Method:</li> <li>Threaded hole single group</li> <li>Winding Function And Quantity:</li> <li>1 primary single component</li> <li>Test Data Document:</li> <li>13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)</li> <li>Thread Series Designator:</li> <li>Unc single group</li> <li>Terminal Type And Quantity:</li> <li>3 pin</li> </ul>
<ul> <li>Distance Between Mounting Facility Centers:</li> <li>0.625 inches single mounting facility single center group</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Quantity:</li> <li>2 single group</li> <li>Mounting Method:</li> <li>Threaded hole single group</li> <li>Winding Function And Quantity:</li> <li>1 primary single component</li> <li>Test Data Document:</li> <li>13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)</li> <li>Thread Series Designator:</li> <li>Unc single group</li> <li>Terminal Type And Quantity:</li> <li>3 pin</li> </ul>
<ul> <li>0.625 inches single mounting facility single center group</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Quantity:</li> <li>2 single group</li> <li>Mounting Method:</li> <li>Threaded hole single group</li> <li>Winding Function And Quantity:</li> <li>1 primary single component</li> <li>Test Data Document:</li> <li>13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)</li> <li>Thread Series Designator:</li> <li>Unc single group</li> <li>Terminal Type And Quantity:</li> <li>3 pin</li> </ul>
Inclosure Type:         Hermetically sealed         Mounting Facility Quantity:         2 single group         Mounting Method:         Threaded hole single group         Winding Function And Quantity:         1 primary single component         Test Data Document:         13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Thread Series Designator:         Unc single group         Terminal Type And Quantity:         3 pin
Hermetically sealed   Mounting Facility Quantity:   2 single group   Mounting Method:   Threaded hole single group   Winding Function And Quantity:   1 primary single component   Test Data Document:   13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing)   etc:; excludes any specification, standard or other document that may be referenced in a basic governing drawing)   Thread Series Designator:   Unc single group   Terminal Type And Quantity:   3 pin
Mounting Facility Quantity:         2 single group         Mounting Method:         Threaded hole single group         Winding Function And Quantity:         1 primary single component         Test Data Document:         1 3499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing)         etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Thread Series Designator:         Unc single group         Terminal Type And Quantity:         3 pin
<ul> <li>2 single group</li> <li>Mounting Method:</li> <li>Threaded hole single group</li> <li>Winding Function And Quantity: <ul> <li>1 primary single component</li> </ul> </li> <li>Test Data Document: <ul> <li>13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)</li> <li>Thread Series Designator: <ul> <li>Unc single group</li> <li>Terminal Type And Quantity:</li> <li>3 pin</li> </ul> </li> </ul></li></ul>
Mounting Method:         Threaded hole single group         Winding Function And Quantity:         1 primary single component         Test Data Document:         13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Thread Series Designator:         Unc single group         Terminal Type And Quantity:         3 pin
<ul> <li>Threaded hole single group</li> <li>Winding Function And Quantity: <ol> <li>primary single component</li> </ol> </li> <li>Test Data Document: <ol> <li>13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)</li> </ol> </li> <li>Thread Series Designator: <ol> <li>Unc single group</li> <li>Terminal Type And Quantity:</li> <li>3 pin</li> </ol> </li> </ul>
<ul> <li>Winding Function And Quantity:</li> <li>1 primary single component</li> <li>Test Data Document:</li> <li>13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)</li> <li>Thread Series Designator:</li> <li>Unc single group</li> <li>Terminal Type And Quantity:</li> <li>3 pin</li> </ul>
<ul> <li>1 primary single component</li> <li>Test Data Document:</li> <li>13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)</li> <li>Thread Series Designator:</li> <li>Unc single group</li> <li>Terminal Type And Quantity:</li> <li>3 pin</li> </ul>
Test Data Document:         13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)         Thread Series Designator:         Unc single group         Terminal Type And Quantity:         3 pin
13499-278-0783-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) <b>Thread Series Designator:</b> Unc single group <b>Terminal Type And Quantity:</b> 3 pin
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) <b>Thread Series Designator:</b> Unc single group <b>Terminal Type And Quantity:</b> 3 pin
Thread Series Designator:         Unc single group         Terminal Type And Quantity:         3 pin
Unc single group Terminal Type And Quantity: 3 pin
Terminal Type And Quantity: 3 pin
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0