## NSN 5950-00-076-7715

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-076-7715

view Offiline at https://aerobasegroup.com/hsh/0550-00-070-7710
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.235 inches single mounting facility single center group and 1.265 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.735 inches single mounting facility single center group and 0.765 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Three phase to single phase single component and three phase to three phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
2.938 inches
Body Width:
1.313 inches
Body Height:
2.250 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Thread Size:
0.138 inches single group
Winding Operating Current:
25.0 milliamperes ac single component 2nd secondary
Winding Operating Voltage:
6.00 ac volts single component 2nd secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
9 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<u></u>

No

Demilitarization:

## NSN 5950-00-076-7715

Power Transformer - Page 2 of 2



Fiig:

A058b0