

View Online at <https://aerobasegroup.com/nsn/5950-00-076-7715>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.235 inches single mounting facility single center group and 1.265 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.735 inches single mounting facility single center group and 0.765 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to three phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.938 inches

Body Width:

1.313 inches

Body Height:

2.250 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

25.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

6.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0