

View Online at <https://aerobasegroup.com/nsn/5950-00-078-6205>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.880 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.880 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

2.875 inches

Body Width:

2.719 inches

Body Height:

3.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

1.2 amperes ac single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0