

View Online at <https://aerobasegroup.com/nsn/5950-00-078-9236>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.190 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.190 inches single mounting facility single center group

Overall Height:

2.750 inches

Frequency Rating:

376.0 hertz single component and 424.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.625 inches

Body Width:

1.625 inches

Body Height:

2.375 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

2.2 milliamperes ac single component single secondary

Winding Operating Voltage:

41.00 ac volts single component single secondary

Test Data Document:

10001-2548764 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0