

View Online at <https://aerobasegroup.com/nsn/5950-00-078-9238>

**Reliability Indicator:**

Not established

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

**Body Length:**

1.750 inches

**Body Width:**

1.281 inches

**Body Height:**

1.938 inches

**Distance Between Mounting Facility Centers:**

1.312 inches single mounting facility single center group

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.112 inches single group

**Winding Operating Current:**

5.3 milliamperes dc single component single primary

**Winding Operating Voltage:**

1.53 ac volts single component single secondary and 5.13 ac volts single component single secondary and 27.90 ac volts single component single secondary and 42.91 ac volts single component single secondary and 48.21 ac volts single component single secondary and 66.29 ac volts single component single secondary

**Test Data Document:**

10001-2548770 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

10 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0