

View Online at <https://aerobasegroup.com/nsn/5950-00-078-9238>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

1.750 inches

Body Width:

1.281 inches

Body Height:

1.938 inches

Distance Between Mounting Facility Centers:

1.312 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

5.3 milliamperes dc single component single primary

Winding Operating Voltage:

1.53 ac volts single component single secondary and 5.13 ac volts single component single secondary and 27.90 ac volts single component single secondary and 42.91 ac volts single component single secondary and 48.21 ac volts single component single secondary and 66.29 ac volts single component single secondary

Test Data Document:

10001-2548770 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0