## NSN 5950-00-079-1530

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-079-1530

Dell'al-little la disease
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.750 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.875 inches single mounting facility single center group
Mounting Hole Diameter:
0.265 inches single group
Frequency Rating:
380.0 hertz single component and 420.0 hertz single component
Input-output Phase Relationship:
Three phase to six phase single component
Transformer Winding Connection Type:
Wye-wye
Body Length:
6.500 inches
Body Width:
4.375 inches
Body Height:
2.875 inches
Inclosure Type:
Open
Open Mounting Facility Quantity:
Mounting Facility Quantity:
Mounting Facility Quantity: 4 single group
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity:
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Winding Operating Voltage:
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary  Terminal Type And Quantity:
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary  Terminal Type And Quantity: 10 wire lead w/lug
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary  Terminal Type And Quantity: 10 wire lead w/lug  Shelf Life: N/a
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary  Terminal Type And Quantity: 10 wire lead w/lug  Shelf Life:
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary  Terminal Type And Quantity: 10 wire lead w/lug  Shelf Life: N/a  Unit Of Measure:
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary  Terminal Type And Quantity: 10 wire lead w/lug  Shelf Life: N/a  Unit Of Measure:  Demilitarization:
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary  Terminal Type And Quantity: 10 wire lead w/lug  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No
Mounting Facility Quantity: 4 single group  Mounting Method: Flange single group and unthreaded hole single group  Winding Function And Quantity: 1 primary single component and 1 secondary single component  Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary  Terminal Type And Quantity: 10 wire lead w/lug  Shelf Life: N/a  Unit Of Measure:  Demilitarization: