NSN 5950-00-079-1530

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-079-1530

| Dell'al-little la disease |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.875 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.265 inches single group |
| Frequency Rating: |
| 380.0 hertz single component and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to six phase single component |
| Transformer Winding Connection Type: |
| Wye-wye |
| Body Length: |
| 6.500 inches |
| Body Width: |
| 4.375 inches |
| Body Height: |
| 2.875 inches |
| Inclosure Type: |
| |
| Open |
| Open Mounting Facility Quantity: |
| |
| Mounting Facility Quantity: |
| Mounting Facility Quantity: 4 single group |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary Terminal Type And Quantity: |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary Terminal Type And Quantity: 10 wire lead w/lug |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary Terminal Type And Quantity: 10 wire lead w/lug Shelf Life: N/a |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary Terminal Type And Quantity: 10 wire lead w/lug Shelf Life: |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary Terminal Type And Quantity: 10 wire lead w/lug Shelf Life: N/a Unit Of Measure: |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary Terminal Type And Quantity: 10 wire lead w/lug Shelf Life: N/a Unit Of Measure: Demilitarization: |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary Terminal Type And Quantity: 10 wire lead w/lug Shelf Life: N/a Unit Of Measure: Demilitarization: No |
| Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Voltage: 19.95 ac volts single component single secondary and 22.30 ac volts single component single secondary Terminal Type And Quantity: 10 wire lead w/lug Shelf Life: N/a Unit Of Measure: Demilitarization: |