

View Online at <https://aerobasegroup.com/nsn/5950-00-079-5416>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.250 inches single mounting facility single center group

Mounting Slot Width:

0.281 inches single group

Frequency Rating:

47.5 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

5.500 inches

Body Width:

5.375 inches

Body Height:

5.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

10.0 amperes ac single component single secondary

Winding Operating Voltage:

25.00 ac volts single component single secondary

Test Data Document:

08440-510-0441 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

8 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0