Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-080-2107

Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 2.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.810 inches single mounting facility single center group Mounting Hole Diameter: 0.219 inches single group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.463 inches Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Minding Operating Current: 4.3 amperes ac single component single primary input Terminal Type And Quantity: 3 threaded stud Shef Life: Na Unit Of Measure: C Demilitarization: No Elig: Aosebo	Reliability Indicator:
Center To Center Distance Between Mounting Facilities Parallel To Length: 2.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.810 inches single mounting facility single center group Mounting Hole Diameter: 0.219 inches single group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.463 inches Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Fucility Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Minedia Guantity: 3 threaded stud Shelf Life: N/a Dire Measure: - Demilitarization: No Fig:	-
2.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.810 inches single mounting facility single center group Mounting Hole Diameter: 0.219 inches single group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.463 inches Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding And Quantity: 3 threaded stud Sheff Life: Na Unit of Measure: - Demilitarization: No Fig:	
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.810 inches: single mounting facility single center group Mounting Hole Diameter: 0.219 inches: single group Frequency Rating: 380.0 hertz: single component and 420.0 hertz: single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.463 inches Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac: single component single primary input Winding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Winding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 115.00 ac volts: single component single primary input Minding Operating Voltage: 11	
1.810 inches single mounting facility single center group Mounting Hole Diameter: 0.219 inches single group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.463 inches Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Minding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Sheed Stud Sheef Life: Na Unit Of Measure: - Demilitarization: No	
Mounting Hole Diameter:         0.219 inches single group         Frequency Rating:         380.0 hertz single component and 420.0 hertz single component         Input-output Phase Relationship:         Single phase to single phase single component         Body Length:         2.463 inches         Body Width:         1.750 inches         Body Height:         2.625 inches         Inclosure Type:         Fully enclosed         Mounting Facility Quantity:         4 single group         Mounting function And Quantity:         1 primary, fixed autotransformer type single component         Winding Function And Quantity:         1 primary, fixed autotransformer type single component         Winding Operating Current:         4.3 amperes ac single component single primary input         Winding Operating Voltage:         115.00 ac volts single component single primary input         Terminal Type And Quantity:         3 threaded stud         Sheff Life:         N/a         Unit Of Measure:         -         Demilitarization:         No         Fig:	-
0.219 inches single group Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.463 inches Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Mounting Method: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.463 inches Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Sheff Life: N/a Unit Of Measure:  Demilitarization: No Flig:	
380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.463 inches Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Sheff Life: N/a Unit Of Measure: 	
Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.463 inches Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Sheff Life: N/a Unit Of Measure: 	
Single phase to single phase single component Body Length: 2.463 inches Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	
Body Length: 2.463 inches Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	
2.463 inches Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Minding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Sheff Life: N/a Demilitarization: No Fig:	
Body Width: 1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Operating Voltage: 115.00 ac volts single component single primary input Minding Ope	
1.750 inches Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Minding Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	
Body Height: 2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Minding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	-
2.625 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Inclosure Type: Fully enclosed Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Flange single group and unthreaded hole single group Minding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Init Of Measure:  Demilitarization: No Fig:	
Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Vinding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Vinding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	
4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	-
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	
Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	-
1 primary, fixed autotransformer type single component Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Winding Function And Quantity:
Winding Operating Current: 4.3 amperes ac single component single primary input Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Winding Operating Voltage: 115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	
115.00 ac volts single component single primary input Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	4.3 amperes ac single component single primary input
Terminal Type And Quantity: 3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Winding Operating Voltage:
3 threaded stud Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	115.00 ac volts single component single primary input
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure:  Demilitarization: No Fiig:	3 threaded stud
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A058b0	Filg:
	A058b0