Power Autotransformer Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-080-3037

| Poliobility Indicatory |
|---|
| Reliability Indicator: Not established |
| |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.297 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.859 inches single mounting facility single center group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.062 inches |
| Body Width: |
| 2.625 inches |
| Body Height: |
| 4.250 inches |
| Maximum Operating Temp: |
| 105.0 degrees celsius |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary, fixed autotransformer type single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.164 inches single group |
| Winding Operating Current: |
| 4.4 amperes ac single component single primary input |
| Winding Operating Voltage: |
| 121.00 ac volts single component single primary input |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 6 standoff, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |



Demilitarization:

No

Fiig:

A058b0