

View Online at <https://aerobasegroup.com/nsn/5950-00-080-4754>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.688 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

4.690 inches

Body Width:

4.000 inches

Body Height:

6.640 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

265.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

280.00 ac volts single component 4th secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

20 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0