

View Online at <https://aerobasegroup.com/nsn/5950-00-080-9620>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Overall Height:

4.562 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.750 inches

Body Width:

2.375 inches

Body Height:

3.812 inches

Maximum Operating Temp:

85.0 degrees celsius

End Application:

S-3b viking, f4s aircraft, f-14 tomcat, ea-6b prowler aircraft. Mh-53e, h-3 sea king, sh-60b lamps mark iii, ch-53a/d/e helicopters.

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

3.0 amperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

25.50 ac volts single component single secondary

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0