Radio Frequency Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-081-1321

| Poliobility Indicatory  |
|---|
| Reliability Indicator:  |
| Not established   |
| Overall Length:   |
| 0.490 inches  |
| Inductance Rating:  |
| 0.80 microhenries single component single secondary               |
| Frequency Rating:   |
| 25.0 megahertz single component                                   |
| Coil Form Type:   |
| Hollow single component   |
| Adjustment Device Drive Type:                                     |
| Slotted screw single component                                    |
| Overall Diameter:   |
| Between 0.417 inches and 0.427 inches                             |
| Distance Between Mounting Facility Centers:                       |
| 0.422 inches single mounting facility single center group         |
| Mounting Tab Width:   |
| Between 0.058 inches and 0.060 inches                             |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Tab single group  |
| Rating Method:  |
| Electrical single component single secondary                      |
| Winding Function And Quantity:                                    |
| 1 primary single component and 1 secondary single component       |
| Winding Conductor Size:   |
| 0.01003 inches american wire gage single component single primary |
| Adjustment Method And Quantity:                                   |
| 1 adjustable core single component                                |
| Terminal Type And Quantity:                                       |
| 5 pin   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| -   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A058b0  |
|   |
|   |