NSN 5950-00-081-3085

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-081-3085

| Reliability Indicator: | | |
|------------------------|--|-------|
| Not established | | |
| | | _ |

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.313 inches single mounting facility single center group

Overall Height:

5.000 inches

Overall Width:

3.687 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.312 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

8.5 amperes ac single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component 1st secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

1 tab, solder lug and 10 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-00-081-3085

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0