

View Online at <https://aerobasegroup.com/nsn/5950-00-081-3155>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.380 inches single mounting facility single center group

Mounting Hole Diameter:

0.218 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

4.120 inches

Body Width:

4.120 inches

Body Height:

6.030 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

14.0 amperes ac single component single secondary

Winding Operating Voltage:

5.00 ac volts single component single secondary

Special Features:

Tube socket with clamping ring for type 576a tube mtd on top of transformer case. Extra terminal marked dc internally connected to output term marked f1

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0