

View Online at <https://aerobasegroup.com/nsn/5950-00-082-1616>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.688 inches single mounting facility single center group

Frequency Rating:

45.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 4.062 inches and 4.312 inches

Body Width:

Between 3.562 inches and 3.688 inches

Body Height:

Between 4.125 inches and 4.312 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

3.0 amperes dc single component 3rd secondary

Winding Operating Voltage:

40.00 ac volts single component 3rd secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0