NSN 5950-00-084-3466

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-084-3466 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.625 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.125 inches single mounting facility single center group |
| Overall Height: |
| 3.688 inches |
| Mounting Hole Diameter: |
| 0.203 inches single group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Body Length: |
| 4.188 inches |
| Body Width: |
| 1.813 inches |
| Body Height: |
| 2.875 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 4 secondary single component |
| Winding Operating Current: |
| 250.0 microamperes ac single component 4th secondary |
| Winding Operating Voltage: |
| 440.00 ac volts single component single primary |
| Terminal Type And Quantity: |
| 15 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5950-00-084-3466

Power Transformer - Page 2 of 2



Fiig:

A058b0