## NSN 5950-00-086-0339

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-086-0339

Reliability	Indicator:
Not established	
Center To	Center Distance Between Mounting Facilities Parallel To Length:
3.750 inch	es single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:	
2.125 inch	es single mounting facility single center group
Frequency	/ Rating:
60.0 hertz	single component
Input-outp	out Phase Relationship:
Single pha	se to single phase single component
Winding S	Shielding Method:
Internal sh	ield grounded to inclosure single component
Body Len	gth:
5.190 inch	es
Body Wid	th:
4.420 inch	es
Body Heig	Jht:
4.620 inch	es
Inclosure	Туре:
Hermetical	ly sealed
Mounting Facility Quantity:	
4 single gr	oup
Mounting	Method:
Threaded	stud single group
Winding F	unction And Quantity:
1 primary s	single component and 1 secondary single component
Thready C	tty Per Inch (tpi):
20 single g	roup
Thread Siz	ze:
0.250 inch	es single group
Winding C	Operating Current:
550.0 millia	amperes ac single component single secondary
Winding Operating Voltage:	
339.00 ac volts single component single secondary	
Thread Se	ries Designator:
Unc single	group
Terminal 1	Type And Quantity:

Unit Of Measure:

N/a

Shelf Life:

4 standoff, solder lug

## NSN 5950-00-086-0339

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0