NSN 5950-00-086-0528

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-086-0528

Reliability	Indicator:
-------------	------------

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.670 inches single mounting facility single center group and 1.710 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.420 inches single mounting facility single center group and 1.460 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.420 inches

Body Width:

2.170 inches

Body Height:

2.560 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

1.0 amperes ac single component single secondary

Winding Power Rating:

6.3 volts-amperes single component single secondary

Winding Operating Voltage:

6.30 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-00-086-0528

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0