NSN 5950-00-086-1826

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-086-1826

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.875 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

6.750 inches

Body Width:

5.750 inches

Body Height:

6.250 inches

End Application:

Arsr-1, ca-4087 power supply

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.312 inches single group

Winding Operating Current:

318.0 milliamperes ac single component single secondary

Winding Operating Voltage:

1.10 ac kilovolts single component single secondary

Special Features:

Hv transformer; function, tranformer, power, set-up; reference data, t6802, instruction book, arsr-1d/e/f, vol 5, sec 10, pg 10-609

Thread Series Designator:

Uns single group

Terminal Type And Quantity:

7 standoff, solder lug

Shelf Life:

N/a

NSN 5950-00-086-1826

Power Transformer - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0