NSN 5950-00-086-9143

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-086-9143 |
|---------------------------------------------------------------------------|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.750 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.188 inches single group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Body Length: |
| 2.975 inches |
| Body Width: |
| 2.880 inches |
| Body Height: |
| 3.630 inches |
| Maximum Operating Temp: |
| 85.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and slot single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 5.2 amperes ac single component single secondary |
| Winding Operating Voltage: |
| 6.30 ac volts single component single secondary |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |

No

Demilitarization:

NSN 5950-00-086-9143

Power Transformer - Page 2 of 2



Fiig:

A058b0