

View Online at <https://aerobasegroup.com/nsn/5950-00-086-9888>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.120 inches single mounting facility single center group

Mounting Hole Diameter:

0.223 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Body Length:

3.120 inches

Body Width:

3.190 inches

Body Height:

3.120 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Voltage:

26.00 ac volts single component single secondary and 55.00 ac volts single component single secondary and 85.00 ac volts single component single secondary and 95.00 ac volts single component single secondary and 110.00 ac volts single component single secondary and 133.00 ac volts single component single secondary and 135.00 ac volts single component single secondary and 145.00 ac volts single component single secondary and 165.00 ac volts single component single secondary and 185.00 ac volts single component single secondary

Terminal Type And Quantity:

34 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0