NSN 5950-00-087-3548

Reactor - Page 1 of 2

Reliability Indicator:

Not established

Inductance Type:

Inductance Rating:

Fixed



View Online at https://aerobasegroup.com/nsn/5950-00-087-3548

2.438 inches single mounting facility single center group

3.000 inches single mounting facility single center group

10.00 millihenries single component single winding

Center To Center Distance Between Mounting Facilities Parallel To Length:

Center To Center Distance Between Mounting Facilities Parallel To Width:

Body Length:					
3.940 inches					
Body Width:					
3.380 inches					
Body Height:					
5.250 inches					
Maximum Operating Temp:					
105.0 degrees celsius					
Winding Quantity:					
1 single component					
Inclosure Type:					
Hermetically sealed					
Mounting Facility Quantity:					
4 single group					
Mounting Method:					
Threaded stud single group					
Rating Method:					
Rating Method: Electrical single component single winding					
-					
Electrical single component single winding					
Electrical single component single winding Thready Qty Per Inch (tpi):					
Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group					
Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size:					
Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group					
Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current:					
Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 10.0 amperes dc single component single winding					
Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms:					
Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.175 single component single winding					
Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.175 single component single winding Thread Series Designator:					
Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.175 single component single winding Thread Series Designator: Unc single group					
Electrical single component single winding Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.175 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity:					

NSN 5950-00-087-3548

Reactor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A058b0