## NSN 5950-00-087-5794

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-087-5794

Not established Turn Quantity: 975 single component single winding Inductance Rating: 220.00 microhenries single component single winding Coil Form Type: Hollow single component Core Construction: Powdered single component Adjustment Device Drive Type: Slotted screw single component Body Length: 0.500 inches Overall Diameter: 0.400 inches Unclosure Type: Fully enclosed Mounting Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00353 inches american wire gage single component single winding Winding Operating Current: 16.0.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	
Turn Quantity: 975 single component single winding Inductance Rating: 220.00 microhenries single component single winding Coil Form Type: Hollow single component Core Construction: Powdered single component Adjustment Device Drive Type: Slotted screw single component Body Length: 0.500 inches Overall Diameter: 0.400 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00353 inches american wire gage single component single winding Winding Operating Current: 160.0 milliamperes de single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	Reliability Indicator:
975 single component single winding Inductance Rating: 220.00 microhenries single component single winding Coil Form Type: Hollow single component Core Construction: Powdered single component Adjustment Device Drive Type: Slotted screw single component Body Length: 0.500 inches Overall Diameter: 0.400 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00353 inches american wire gage single component single winding Winding Operating Current: 160.0 milliamperes de single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	
Inductance Rating:  220.00 microhenries single component single winding  Coil Form Type: Hollow single component  Core Construction: Powdered single component  Adjustment Device Drive Type: Slotted screw single component  Body Length: 0.500 inches  Overall Diameter: 0.400 inches  Inclosure Type: Fully enclosed  Mounting Method: Terminal single group  Rating Method: Electrical single component single winding and winding turns single component single winding  Winding Conductor Size: 0.00353 inches american wire gage single component single winding  Dc Resistance Rating In Ohms: 15.000 single component single winding  Quality Factor: 50 single component single winding  Adjustment Method And Quantity: 1 adjustable core single component  Special Features: Quality controlled for polaris  Terminal Type And Quantity: 2 wire lead  Shelf Life:	
220.00 microhenries single component single winding  Coil Form Type: Hollow single component  Core Construction: Powdered single component  Adjustment Device Drive Type: Slotted screw single component  Body Length: 0.500 inches  Overall Diameter: 0.400 inches  Inclosure Type: Fully enclosed  Mounting Method: Terminal single group  Rating Method: Electrical single component single winding and winding turns single component single winding  Winding Conductor Size: 0.00353 inches american wire gage single component single winding  Winding Operating Current: 160.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 15.000 single component single winding  Adjustment Method And Quantity: 1 adjustable core single component  Special Features: Quality controlled for polaris  Terminal Type And Quantity: 2 wire lead  Shelf Life:	
Coil Form Type: Hollow single component Core Construction: Powdered single component Adjustment Device Drive Type: Slotted screw single component Body Length: 0.500 inches Overall Diameter: 0.400 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00353 inches american wire gage single component single winding Winding Operating Current: 160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding Quality Factor: 50 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	
Hollow single component  Core Construction: Powdered single component  Adjustment Device Drive Type: Slotted screw single component  Body Length: 0.500 inches  Overall Diameter: 0.400 inches  Inclosure Type: Fully enclosed  Mounting Method: Terminal single group  Rating Method: Electrical single component single winding and winding turns single component single winding  Winding Conductor Size: 0.00353 inches american wire gage single component single winding  Winding Operating Current: 160.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 15.000 single component single winding  Adjustment Method And Quantity: 1 adjustable core single component  Special Features: Quality controlled for polaris  Terminal Type And Quantity: 2 wire lead  Shelf Life:	220.00 microhenries single component single winding
Core Construction: Powdered single component Adjustment Device Drive Type: Slotted screw single component Body Length: 0.500 inches Overall Diameter: 0.400 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00353 inches american wire gage single component single winding Winding Operating Current: 160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	Coil Form Type:
Powdered single component  Adjustment Device Drive Type: Slotted screw single component  Body Length: 0.500 inches  Overall Diameter: 0.400 inches  Inclosure Type: Fully enclosed  Mounting Method: Terminal single group  Rating Method: Electrical single component single winding and winding turns single component single winding  Winding Conductor Size: 0.00353 inches american wire gage single component single winding  Winding Operating Current: 160.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 15.000 single component single winding  Quality Factor: 50 single component single winding  Adjustment Method And Quantity: 1 adjustable core single component  Special Features: Quality controlled for polaris  Terminal Type And Quantity: 2 wire lead  Shelf Life:	Hollow single component
Adjustment Device Drive Type:  Slotted screw single component  Body Length:  0.500 inches  Overall Diameter: 0.400 inches  Inclosure Type: Fully enclosed  Mounting Method: Terminal single group  Rating Method: Electrical single component single winding and winding turns single component single winding  Winding Conductor Size: 0.00353 inches american wire gage single component single winding  Winding Operating Current: 160.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 15.000 single component single winding  Quality Factor: 50 single component single winding  Adjustment Method And Quantity: 1 adjustable core single component  Special Features: Quality controlled for polaris  Terminal Type And Quantity: 2 wire lead  Shelf Life:	Core Construction:
Slotted screw single component  Body Length:  0.500 inches  Overall Diameter: 0.400 inches  Inclosure Type: Fully enclosed  Mounting Method: Terminal single group  Rating Method: Electrical single component single winding and winding turns single component single winding  Winding Conductor Size: 0.00353 inches american wire gage single component single winding  Winding Operating Current: 160.0 milliamperes do single component single winding  Do Resistance Rating In Ohms: 15.000 single component single winding  Quality Factor: 50 single component single winding  Adjustment Method And Quantity: 1 adjustable core single component  Special Features: Quality controlled for polaris  Terminal Type And Quantity: 2 wire lead  Shelf Life:	Powdered single component
Body Length:  0.500 inches  Overall Diameter: 0.400 inches  Inclosure Type: Fully enclosed  Mounting Method: Terminal single group  Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00353 inches american wire gage single component single winding Winding Operating Current: 160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding  Quality Factor: 50 single component single winding  Adjustment Method And Quantity: 1 adjustable core single component  Special Features: Quality controlled for polaris  Terminal Type And Quantity: 2 wire lead  Shelf Life:	Adjustment Device Drive Type:
Overall Diameter:  0.400 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00353 inches american wire gage single component single winding Winding Operating Current: 160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding Quality Factor: 50 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	Slotted screw single component
Overall Diameter:  0.400 inches Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00353 inches american wire gage single component single winding Winding Operating Current: 160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding Quality Factor: 50 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	Body Length:
Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00353 inches american wire gage single component single winding Winding Operating Current: 160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding Quality Factor: 50 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	0.500 inches
Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00353 inches american wire gage single component single winding Winding Operating Current: 160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding Quality Factor: 50 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	Overall Diameter:
Fully enclosed  Mounting Method: Terminal single group  Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00353 inches american wire gage single component single winding Winding Operating Current: 160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding Quality Factor: 50 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	0.400 inches
Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00353 inches american wire gage single component single winding Winding Operating Current: 160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding Quality Factor: 50 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	Inclosure Type:
Rating Method:  Electrical single component single winding and winding turns single component single winding Winding Conductor Size:  0.00353 inches american wire gage single component single winding Winding Operating Current:  160.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.000 single component single winding  Quality Factor:  50 single component single winding  Adjustment Method And Quantity:  1 adjustable core single component  Special Features:  Quality controlled for polaris  Terminal Type And Quantity:  2 wire lead  Shelf Life:	Fully enclosed
Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size:  0.00353 inches american wire gage single component single winding Winding Operating Current:  160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms:  15.000 single component single winding Quality Factor:  50 single component single winding Adjustment Method And Quantity:  1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity:  2 wire lead Shelf Life:	Mounting Method:
Electrical single component single winding and winding turns single component single winding Winding Conductor Size:  0.00353 inches american wire gage single component single winding Winding Operating Current:  160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms:  15.000 single component single winding Quality Factor:  50 single component single winding Adjustment Method And Quantity:  1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity:  2 wire lead Shelf Life:	Terminal single group
Winding Conductor Size:  0.00353 inches american wire gage single component single winding Winding Operating Current:  160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms:  15.000 single component single winding Quality Factor:  50 single component single winding Adjustment Method And Quantity:  1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity:  2 wire lead Shelf Life:	Rating Method:
0.00353 inches american wire gage single component single winding Winding Operating Current: 160.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.000 single component single winding Quality Factor: 50 single component single winding Adjustment Method And Quantity: 1 adjustable core single component Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	Electrical single component single winding and winding turns single component single winding
Winding Operating Current:  160.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.000 single component single winding  Quality Factor:  50 single component single winding  Adjustment Method And Quantity:  1 adjustable core single component  Special Features:  Quality controlled for polaris  Terminal Type And Quantity:  2 wire lead  Shelf Life:	Winding Conductor Size:
160.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.000 single component single winding  Quality Factor:  50 single component single winding  Adjustment Method And Quantity:  1 adjustable core single component  Special Features:  Quality controlled for polaris  Terminal Type And Quantity:  2 wire lead  Shelf Life:	0.00353 inches american wire gage single component single winding
Dc Resistance Rating In Ohms:  15.000 single component single winding  Quality Factor:  50 single component single winding  Adjustment Method And Quantity:  1 adjustable core single component  Special Features:  Quality controlled for polaris  Terminal Type And Quantity:  2 wire lead  Shelf Life:	Winding Operating Current:
15.000 single component single winding  Quality Factor:  50 single component single winding  Adjustment Method And Quantity:  1 adjustable core single component  Special Features:  Quality controlled for polaris  Terminal Type And Quantity:  2 wire lead  Shelf Life:	160.0 milliamperes dc single component single winding
Quality Factor:  50 single component single winding  Adjustment Method And Quantity:  1 adjustable core single component  Special Features:  Quality controlled for polaris  Terminal Type And Quantity:  2 wire lead  Shelf Life:	Dc Resistance Rating In Ohms:
50 single component single winding  Adjustment Method And Quantity:  1 adjustable core single component  Special Features:  Quality controlled for polaris  Terminal Type And Quantity:  2 wire lead  Shelf Life:	15.000 single component single winding
Adjustment Method And Quantity:  1 adjustable core single component  Special Features: Quality controlled for polaris  Terminal Type And Quantity:  2 wire lead  Shelf Life:	Quality Factor:
1 adjustable core single component  Special Features: Quality controlled for polaris  Terminal Type And Quantity: 2 wire lead  Shelf Life:	50 single component single winding
Special Features: Quality controlled for polaris Terminal Type And Quantity: 2 wire lead Shelf Life:	Adjustment Method And Quantity:
Quality controlled for polaris  Terminal Type And Quantity:  2 wire lead  Shelf Life:	1 adjustable core single component
Terminal Type And Quantity: 2 wire lead Shelf Life:	Special Features:
2 wire lead Shelf Life:	Quality controlled for polaris
Shelf Life:	Terminal Type And Quantity:
	2 wire lead
	Shelf Life:
N/a	N/a
Unit Of Measure:	Unit Of Measure:

Demilitarization:

No

## NSN 5950-00-087-5794

Radio Frequency Coil - Page 2 of 2



Fiig:

A058b0