## NSN 5950-00-087-6651

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-087-6651

| 5   |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.500 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 4.000 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 47.5 hertz single component and 63.0 hertz single component               |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 4.938 inches  |
| Body Width:   |
| 4.188 inches  |
| Body Height:  |
| 5.500 inches  |
| Maximum Operating Temp:   |
| 65.0 degrees celsius  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 6 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.190 inches single group   |
| Winding Operating Current:  |
| 220.0 milliamperes dc single component single secondary                   |
| Winding Operating Voltage:  |
| 757.00 ac volts single component single secondary                         |
| Thread Series Designator:   |
| Unf single group  |
| Terminal Type And Quantity:   |
| 4 standoff insulator  |
| Shelf Life:   |
| N/a   |
| Unit Of Maggura:  |

--

## NSN 5950-00-087-6651

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0