NSN 5950-00-088-2620

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-088-2620

| Reliability Indica | ator: |
|---------------------|---|
| Not established | |
| Mounting Hole D | Diameter: |
| 0.187 inches sing | gle group |
| Frequency Ratin | ng: |
| 400.0 hertz singl | le component |
| Input-output Pha | ase Relationship: |
| Single phase to s | single phase single component |
| Body Length: | |
| Between 2.031 in | nches and 2.093 inches |
| Body Width: | |
| 1.250 inches | |
| Body Height: | |
| 1.250 inches | |
| Distance Betwee | en Mounting Facility Centers: |
| 1.719 inches sing | gle mounting facility single center group and 1.750 inches single mounting facility single center group |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Facilit | ty Quantity: |
| 2 single group | |
| Mounting Metho | od: |
| Unthreaded hole | single group |
| Winding Function | on And Quantity: |
| 1 primary single of | component and 1 secondary single component |
| Winding Operati | ing Current: |
| 52.0 milliamperes | s ac single component single secondary |
| Winding Operati | ing Voltage: |
| 36.00 ac volts sir | ngle component single primary |
| Terminal Type A | And Quantity: |
| 5 tab, solder lug | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure | 2: |
| | |
| Demilitarization: | : |
| No | |
| Fiig: | |
| A058b0 | |