

| NSN 5950-00-089-4384 Power Transformer - Page 1 of 2 | Ae |
|---|----|
| View Online at https://aerobasegroup.com/nsn/5950-00-089-4384 | |
| Thread Direction (non-core): | |
| Err-070 | |
| Reliability Indicator: | |
| Not established | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | |
| 3.000 inches single mounting facility single center group | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: | |
| 2.438 inches single mounting facility single center group | |
| Overall Height: | |
| 5.770 inches | |
| Frequency Rating: | |
| 60.0 hertz single component | |
| Input-output Phase Relationship: | |
| Three phase to three phase single component | |
| Transformer Winding Connection Type: | |
| Delta-wye | |
| Maximum Transformer Power Rating: | |
| 705.0 volt-ampere single component | |
| Winding Shielding Method: | |
| Internal shield grounded to inclosure single component | |
| Body Length: | |
| 3.940 inches | |
| Body Width: | |
| 3.380 inches | |

Body Height: 5.250 inches Inclosure Type: Hermetically sealed

4 single group

32 single group

Thread Size:

Mounting Method:

Mounting Facility Quantity:

Threaded stud single group

Thready Qty Per Inch (tpi):

0.190 inches single group
Winding Operating Current:

Winding Operating Voltage:

Winding Function And Quantity:

1 primary and 1 secondary single component

4.08 amperes ac single component single secondary

208.00 ac volts single component single primary

NSN 5950-00-089-4384

Power Transformer - Page 2 of 2



| Unpackaged Unit Weight (non-core): | |
|------------------------------------|--|
| 10.000 pounds | |
| Thread Series Designator: | |
| Unf single group | |
| Terminal Type And Quantity: | |
| 6 solder stud | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

Fiig: A058b0