## NSN 5950-00-089-5391

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-089-5391

Reliabi	lity Indicator:
Not est	ablished
Center	To Center Distance Between Mounting Facilities Parallel To Length:
2.750 ir	nches single mounting facility single center group
Center	To Center Distance Between Mounting Facilities Parallel To Width:
3.625 ir	nches single mounting facility single center group
Freque	ncy Rating:
50.0 he	rtz single component or 60.0 hertz single component
Input-o	utput Phase Relationship:
Single p	phase to single phase single component
Windin	g Shielding Method:
Internal	shield grounded to inclosure single component
Body L	ength:
3.750 ir	nches
Body V	Vidth:
3.625 ir	nches
Body H	leight:
4.500 ir	nches
Inclosu	іге Туре:
Hermet	ically sealed
Mounti	ng Facility Quantity:
4 single	group
Mounti	ng Method:
Thread	ed stud single group
Windin	g Function And Quantity:
1 prima	ry single component and 3 secondary single component
Thread	y Qty Per Inch (tpi):
32 sing	le group
Thread	Size:
0.190 ir	nches single group
Windin	g Operating Current:
300.0 n	nilliamperes ac single component 3rd secondary
Windin	g Operating Voltage:
600.00	ac volts single component 3rd secondary
Thread	Series Designator:
Unf sing	gle group
Termin	al Type And Quantity:
10 sold	er stud
Shelf L	ife:
N/a	
Unit Of	Measure:

## NSN 5950-00-089-5391

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

