

View Online at <https://aerobasegroup.com/nsn/5950-00-091-9950>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.734 inches single mounting facility single center group and 1.766 inches single mounting facility single center group

Frequency Rating:

45.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

Between 2.625 inches and 2.750 inches

Body Width:

Between 2.365 inches and 2.385 inches

Body Height:

Between 3.624 inches and 3.812 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

300.0 milliamperes dc single component 3rd secondary

Winding Power Rating:

8.34 volts-amperes single component 3rd secondary

Winding Operating Voltage:

27.80 dc volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0