NSN 5950-00-096-2784

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-096-2784

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.750 inches single mounting facility single center group Inductance Type: Fixed Inductance Rating:
Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.750 inches single mounting facility single center group Inductance Type: Fixed Inductance Rating:
3.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.750 inches single mounting facility single center group Inductance Type: Fixed Inductance Rating:
Center To Center Distance Between Mounting Facilities Parallel To Width: 2.750 inches single mounting facility single center group Inductance Type: Fixed Inductance Rating:
2.750 inches single mounting facility single center group Inductance Type: Fixed Inductance Rating:
Inductance Type: Fixed Inductance Rating:
Fixed Inductance Rating:
Inductance Rating:
1.17 henry single component single winding
Body Length:
4.500 inches
Body Width:
3.500 inches
Body Height:
3.938 inches
Winding Quantity:
1 single component
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Rating Method:
Electrical single component single winding
Dc Resistance Rating In Ohms:
12.000 single component single winding
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Unit Of Measure:
 Demilitarization:
No
Fiig: A058b0
7030b0