

View Online at <https://aerobasegroup.com/nsn/5950-00-096-5076>

Reliability Indicator:

Not established

Overall Length:

5.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Width:

4.500 inches

Body Height:

3.813 inches

End Application:

Fire pumps. An/sps-4 (v). Aircraft elevators. Submarine atmosphere control and compressed air/gas. Jp-5 aviation fuels systems. L.P. Compressors. Mk-118 fire control sys. Ssbn. High pressure air compressors. Stream (std. Tensioned replenishment at sea method) .

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

1.1 amperes ac single component all primary

Winding Power Rating:

250.0 volts-amperes single component all primary

Criticality Code Justification:

Feat

Winding Operating Voltage:

220.00 ac volts single component all primary

Special Features:

Weapon system essential

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0