

View Online at <https://aerobasegroup.com/nsn/5950-00-096-5076>

**Reliability Indicator:**

Not established

**Overall Length:**

5.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.750 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Width:**

4.500 inches

**Body Height:**

3.813 inches

**End Application:**

Fire pumps. An/sps-4 (v). Aircraft elevators. Submarine atmosphere control and compressed air/gas. Jp-5 aviation fuels systems. L.P. Compressors. Mk-118 fire control sys. Ssbn. High pressure air compressors. Stream (std. Tensioned replenishment at sea method) .

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

2 primary single component and 1 secondary single component

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

1.1 amperes ac single component all primary

**Winding Power Rating:**

250.0 volts-amperes single component all primary

**Criticality Code Justification:**

Feat

**Winding Operating Voltage:**

220.00 ac volts single component all primary

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0