## NSN 5950-00-100-4557

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-100-4557

Parallel To Length:

Parallel To Width:

R	eliability Indicator:
Ν	lot established
С	enter To Center Distance Between Mounting Facilities Para
2	.187 inches single mounting facility single center group
2	enter To Center Distance Between Mounting Facilities Para
	.562 inches single mounting facility single center group
=	requency Rating:
ł	8.0 hertz single component and 62.0 hertz single component
r	nput-output Phase Relationship:
3	ingle phase to single phase single component
3	ody Length:
,	.688 inches
3	ody Width:
2	.000 inches
3	ody Height:
2	.313 inches
r	nclosure Type:
=	ully enclosed
V	Iounting Facility Quantity:
1	single group
V	Iounting Method:
Γ	hreaded hole single group
٨	Vinding Function And Quantity:
	primary single component and 1 secondary single component
•	hready Qty Per Inch (tpi):
3	2 single group
Г	hread Size:
)	.164 inches single group
٨	Vinding Operating Current:
,	50.0 milliamperes ac single component single secondary
٨	Vinding Operating Voltage:
ô	0.00 ac volts single component single primary
Т	hread Series Designator:
U	Inc single group
Г	erminal Type And Quantity:
5	tab, solder lug
s	helf Life:
-	l/a

## NSN 5950-00-100-4557

Power Transformer - Page 2 of 2

**Fiig:** A058b0

