NSN 5950-00-100-5202

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-100-5202

view Online at https://derobasegroup.com/nsi//3350-00-100-3202
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.438 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.750 inches single mounting facility single center group
Inductance Type:
Swinging
Inductance Rating:
2.00 henry single component single winding and 5.00 henry single component single winding
Frequency Rating:
120.0 hertz single component
Body Length:
4.500 inches
Body Width:
3.875 inches
Body Height:
4.500 inches
Maximum Operating Temp:
200.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Rating Method:
Electrical single component single winding
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.164 inches single group
Winding Operating Current:
24.0 milliamperes dc single component single winding and 140.0 milliamperes dc single component single winding
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:

N/a

NSN 5950-00-100-5202

Reactor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0